



## 过滤板

	Herding DELTA 系列 DELTA² 系列	Herding PRO³ 系列	HSL 系列	HSL-C 系列	Herding BETA 系列	Herding ALPHA 系列
最高操作温度为[°C]	70	70	70	100	160	450
残余粉尘浓度 [mg/Am³]	< 0.1	< 0.1	< 0.1	< 0.1	< 0.5	< 2.0
每个滤芯的过滤面积[m²]	1.10 - 7.10	3.15	0.54 - 7.64	0.89 - 7.64	2.20 - 4.75	3.00
粘性粉尘 (带预涂层)	✓	✓	✓	✓	✓	✓
磨蚀性粉尘	✓	✓	✓	✓	✓	✓
再生 能力	✓	✓	✓	✓	✓	✗
含PTFE (聚四氟乙烯) 涂层	✓	✓	✓	✓	✓	✗
符合VDI 2263的粉尘防爆 区屏障	✓	✓	✓	✓	✓	✗
洁净空气再循环 (取决于粉尘等级)	✓	✓	✓	✓	✓	✓
防静电/耗散设计	✓	✗	✓	✓	✗	✗
非充电版本	✓	✓	✓	✓	✓	✗
欧盟批准的制药/食品行业	✗	✗	✓	✓	✓	✗